

BO-W 300

Wafer Butterfly Valve

Indoor and Outdoor Use

UL, ULC Listed and FM Approved



Specifications

Size : 2 1/2" Through 8"
Working Pressure : 300 PSI (21.5 Bars)
Max. Test Pressure : 600 PSI (43.0 Bars)
Working Temperature : 250°F (120°C)
Factory Installed UL Approved Tampered Switch for Indoor and Outdoor Use

Materials

Body : Ductile Iron, EPDM Encapsulated
Disc : Al-Bronze, Ni-Cr Plated
Stem : Stainless Steel, Hardened & Tempered
Housing : Ductile Iron (ASTM A-536)
Hand Wheel : Ductile Iron (ASTM A-536)

Dimensions

(Unit: mm/inch)

SIZE	A	B	C	D	E	F	G	H
2 1/2"	120(4.72)	85(3.35)	49(1.93)	116(4.57)	150(5.91)	168(6.61)	125(4.92)	9.5(0.37)
3"	127(5.00)	92(3.62)	49(1.93)	132(5.20)	157(6.18)	168(6.61)	125(4.92)	16.0(0.63)
4"	145(5.71)	108(4.25)	55(2.17)	152(5.98)	175(6.89)	168(6.61)	125(4.92)	25.0(0.98)
6"	180(7.09)	145(5.71)	59(2.32)	207(8.15)	210(8.27)	208(8.19)	225(8.86)	45.3(1.78)
8"	204(8.03)	170(6.69)	63(2.48)	262(10.31)	234(9.21)	208(8.19)	225(8.86)	68.5(2.70)

