

Product Name: Soft Touch Medium and Long Handle Tools
 Product #: 9200STM and 9200STL Series
 16" (medium) and 19" (long) overall length


ADJUSTMENT PROCEDURE :

This tool is adjusted at the factory and no further adjustment should be required. Should the tools, through extended use, require adjustment, wear in the parts may be compensated for as follows:

1. Close tool handles until pre-load is reached (this is the point at which jaws butt).
2. Measure the distance between the outside of the handles at the end of the handle grips. Dim X is the correct distance.
3. To increase the pre-load setting, loosen the bottom set screw slightly by turning counter clockwise. Then tighten the top set screw by turning clockwise until the preload distance is DIM X. Tighten the bottom set screw to clamp the setting.
4. Recheck the set distance after making three crimps.
5. Check the crimps with the crimp gauge provide. If satisfactory crimps do not result, the tool is likely worn and should be replaced.

In addition, always remember to:


1. Check tool calibration at least daily. It is recommended that at least the first and last crimp of the day are tested.
2. Never exceed the specified handle distance when adjusting your crimp tool. Premature wear will result.
3. Lubricate linkages on a regular basis to maximize tool life.



CRIMPS CONFORM TO ASTM 1807 GAGING PROCEDURE

1. If GO goes over crimped ring and NO GO does not tool is crimping properly.
2. If GO does not go then handle pre-load must be increased.
3. If GO goes-check NO GO. If NO GO goes ring is overcrimped. Decrease handle pre-load. Recheck.

Gage all crimps as shown to avoid distortion in this area around crimped seam.



PART NUMBER	DESCRIPTION	DIM X
9201STM	3/8"	8"± 1/4"
9202STM	1/2"	8"± 1/4"
9203STM	3/4"	8"± 1/4"
9204STM	1 "	9-1/2± 1/4"
9205STM	1/2" & 3/4"	9 1/2"± 1/4"
9206STM	3/4" & 1/2"	9 1/2"± 1/4"
9207STM	5/8"	8"± 1/4"
9201STL	3/8"	9 1/2"± 1/4"
9202STL	1/2"	9 1/2"± 1/4"
9203STL	3/4"	9 1/2"± 1/4"
9204STL	1"	11"± 1/4"
9205STL	1/2" & 3/4"	10 1/2"± 1/4"
9206STL	3/4" & 1/2"	10 1/2"± 1/4"
9207STL	5/8"	9 1/2" ±1/4"
9208STL	1 1/4"	12 1/4" ±1/4"