

## PC4 Cold Caulking Compound Cord



### Product Description

PC4 AF is a unique cold caulking cord supplied as a ready for use cord. The product is dampened, packed into the joint and tightly consolidated with a hammer and caulking tool to form a solid pressure resistant joint. The fiber reinforcement enables the joint to withstand hydrostatic pressure immediately the product is compacted. The product can accommodate vibration and normal deflection, as well as expansion and contraction caused by temperature variations.

### Composition

PC4 AF consists of a mixture of chemical resistant cements and asbestos free non degradable fibers braided to form a pliable cord.

### Advantages

- > Asbestos free
- > Supplied ready for use, no mixing required
- > Quick and easy to apply
- > Can be used in waste water structures
- > Provide an immediate seal
- > Withstands pressures in excess of 1000 psi (7MPa)
- > Accommodates vibration and normal deflections
- > Resistant to biological degradation

### LynCar Product and description

Part#	Description
2895	2m length
2896	3.125 kg tin

### Guide to Quantities

Joint size (inches)	Lft per tin (Lm per tin)	Lbs per tin (Kg per tin)
¼ x 1 (6 x 25)	36.8 (12.0)	0.19 (0.26)
½ x 1 (12 x 25)	18.4 (5.9)	0.38 (0.53)
½ x 1 ½ (12 x 40)	12.0 (3.7)	0.58 (0.85)
1 x 1 ½ (25 x 40)	6.1 (1.8)	1.15 (1.76)
1 x 2 (25 x 50)	4.5 (1.4)	1.54 (2.2)
1 ½ x 1 ½ (40 x 40)	4.1 (1.1)	1.73 (2.8)