

Toll Free Phone: 800.263.7011
Toll Free Fax: 800.459.6227

Toll Free Phone: 800.361.3773
Fax: 905.625.9481

FEATURES

PRO SEAL PLUS

TEMPERATURE RANGE USE:

Gases:

-15°F (-26°C) to 400°F (204°C)

Liquids:

-15°F (-26°C) to 400°F (204°C)

Brushable to -15°F (-26°C)

PRESSURE RANGE USE:

Gases:

Up to 5,000 PSI (351.5 kg/cm²)

Liquids:

Up to 10,000 PSI (703.1 kg/cm²)

U.S. FEDERAL SPECIFICATIONS:

Power Seal exceeds TT-S-1732

AVAILABLE SIZES:

Stock# Size
Brush Top Can
1 1/2 gal 1.5L
1 1/2 gal 1.5L
Flat Top Can
1 1/2 gal 1.5L

Pail

1 1/2 gal 1.5L

"FBC™ System Compatible indicates that this product has been submitted by the manufacturer for testing, and is monitored on an ongoing basis to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings." The manufacturer also agrees not to change the product after passing the test. "FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation."

PRO SEAL PLUS is specially formulated for the fire protection industry for use on all metal threaded connections, **FlowGuard Gold®**, **Blazemaster®**, and **Corzan®** pipe and fittings.



- **Non-Separating**
- **Grit Free Paste**
- **Non-Hardening**
- **Non-Toxic**
- **Easy Cleanup**
- **Indefinite Shelf Life**
- **Adheres to Oily Threads**

Suitable for use on systems carrying:

Air; Glycerine; Glycol; Steam; Water (hot or cold)