

TALON DRAIN OPENER

DIRECTIONS FOR USE READ DIRECTIONS BEFORE USING

DRAINS: Run hot water to warm lines. Add 1 cup **TALON DRAIN OPENER** slowly and directly into drain opening. Run just enough hot tap water to dissolve all the **TALON DRAIN OPENER**. Do not use boiling water with this product. Let stand for one minute, flush with more hot tap water. To prevent drains from clogging in the future, add ½ to 1 cup of **TALON DRAIN OPENER** once a month. If drain is totally clogged, open drain with a snake to allow at least slight flow, then add **TALON DRAIN OPENER** as directed above.

GREASE TRAPS: Use 2 pounds of **TALON DRAIN OPENER** for every 100 gallon capacity of the grease trap to keep grease traps working properly. Pour in **TALON DRAIN OPENER** slowly, then add hot tap water until it is completely dissolved. Let sit overnight for best results.

TOILET BOWLS AND CHINA FIXTURES:

Follow directions under “**DRAINS**”, but premix each ½ cup **TALON DRAIN OPENER** with 2 cups of cold water before adding to drain. Add **TALON DRAIN OPENER** slowly to the 2 cups of water and stir constantly to avoid a violent exothermic reaction.

SEPTIC SYSTEMS: Use 6 pounds of **TALON DRAIN OPENER** to treat a 500 gallon capacity septic tank. Pour **TALON DRAIN OPENER** along with very hot water down sink or tub drain, run hot water for a minute after all **TALON DRAIN OPENER** is down the drain. Add 6 pounds of **TALON DRAIN OPENER** once per year to help prevent the build up of grease and solid waste in system.

ROOT CONTROL: Add 2 pounds slowly to any drain leading to a root clogged drain. Let water run in drain until **TALON DRAIN OPENER** reaches roots. Let sit overnight then flush with hot tap water. Use monthly to control roots.

APPLICATION PRECAUTIONS

- **READ ENTIRE PRODUCT LABEL AND SAFETY DATA SHEET BEFORE USING PRODUCT.**
- **TALON DRAIN OPENER CONTAINS SODIUM HYDROXIDE.**
- **HIGHLY CORROSIVE. CAN CAUSE SEVERE BURNS AND/OR BLINDNESS.**
- **HARMFUL OR FATAL IF SWALLOWED.**
- **DO NOT MIX WITH ACIDS, BLEACH, ALKALINE OR OTHER CHEMICALS.**
- **KEEP AWAY FROM CHILDREN.**
- **ALWAYS WEAR RUBBER GLOVES AND GOGGLES OR FACE SHIELD WHEN HANDLING TALON DRAIN OPENER.**
- **DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.**
- **DO NOT USE IN DISPOSALS OR MIX IN AN ALUMINUM CONTAINER.**
- **DO NOT USE IF ACIDS OR OTHER CHEMICALS ARE IN THE SYSTEM.**
- **KEEP CONTAINER CLOSED AND TIGHTLY CAPPED WHEN NOT IN USE.**
- **AFTER HANDLING TALON DRAIN OPENER, WASH THOROUGHLY, INCLUDING CONTAMINATED EQUIPMENT, SHOES AND CLOTHING .**
- **NEUTRALIZE IRRITATED SKIN WITH VINEGAR.**
- **WHEN USING, PROVIDE SUFFICIENT VENTILATION TO PREVENT BUILDUP OF VAPORS OR MIST.**
- **STORE IN A COOL DRY AREA OUT OF REACH OF CHILDREN.**
- **DO NOT DROP.**
- **AVOID SPILLS. THIS PRODUCT WILL ATTACK ALL ORGANIC MATERIAL.**
- **USE ORIGINAL CONTAINER ONLY. DO NOT TRANSFER.**
- **FOR SALE, USE, AND STORAGE BY PROFESSIONALS ONLY ! NOT FOR CONSUMER USE.**



LynCar
100 Westcreek Blvd., Unit 2
Brampton, ON L6T 5V7
Canada
Tel: 800.263.7011
Fax: 800.459.6227
Email: sales@lynCar.com

